

signature baselights

Signature Baselights are built to meet or exceed British Standards regulations and sealed to IP67 rating. Through flexibility on product supply, all bases have their own unique application, with options such as photocells and 24V AC. Incorporated into every unit are features such as a UV stabilised Polycarbonate lens, large internal capacity and multiple cable options. Signature are proud of its ability to provide enhanced safety and reduced maintenance through innovations such as Knock Down Warning systems (Safebase and Superbase) and LED illuminated - all as a result of customer partnerships.

	FEATURES	PRODUCT CODES
	<p>BUDGET™ (PF94/BBL)</p> <ul style="list-style-type: none"> 3mm Galvanised Mild Steel Base Domed or Flat Glazed Option Bolt Down or Hinged Lid Option Available 2 x PL11 watt, 3 x PL11 watt, 24V AC 2 x 25mm Cable Gland & Blank – Front Located 	<p>BUDGET™ (PF94/BBL)</p> <p>BL-B-211-H-F 2 X PL11 watt Hinged Lid Flat Glazed</p> <p>BL-B-211-BD-RW 2 x PL11 watt Bolt Down Raised Window</p> <p>BL-B-311-BD-RW 3 x PL11 watt Bolt Down Raised Window</p> <p>Suits all industry standard bollards</p>
	<p>BLBASE12™</p> <ul style="list-style-type: none"> 3mm Galvanised Mild Steel Base Flat Glazed Hinged Lid Available 2 x PL11 watt, 3 x PL11 watt, 24V AC 2 x 25mm Cable Holes Front and Side location 	<p>BLBASE12™</p> <p>BL-BASE12 2 X PL11 watt</p> <p>BL-BASE10 3 x PL11 watt</p> <p>BL-BASE12-24V 2 x PL11 watt - 24V AC</p>
	<p>CITYBASE™</p> <ul style="list-style-type: none"> 3mm Galvanised Mild Steel Base Flat Glazed Hinged Lid Available 2 x PL11 watt, 24V AC Manufactured to suit Cityflex Bollard Shell 2 x 25mm Cable Holes Front and Side location 	<p>CITYBASE™</p> <p>BL-BASE35 2 X PL11 watt</p> <p>BL-BASE37 2 x PL11 watt c/w Selc 101B PECU</p> <p>BL-BASE35-24V 2 x PL11 watt - 24V AC</p> <p>BL-BASE44 2 x PL11 watt - Conv.</p>
	<p>SUREBASE™</p> <ul style="list-style-type: none"> 3mm Galvanised Mild Steel Base Flat Glazed Hinged Lid Available 2 x PL11 watt, 24V AC Manufactured to suit Sureflex Bollard Shell 2 x 25mm Cable Holes Front and Side location 	<p>SUREBASE™</p> <p>BL-BASE27 2 X PL11 watt</p> <p>BL-BASE26 2 x PL11 watt c/w Selc 101B PECU</p> <p>BL-BASE27-24V 2 x PL11 watt - 24V AC</p>
	<p>QUICK ACCESS™</p> <ul style="list-style-type: none"> 3mm Galvanised Mild Steel Base Low Profile Base with Double 1/4 turn replaceable vandal resistant locks Tilt and Lock allows complete removal of bollard with window Available 2 x PL11 watt, 3 x PL11 watt, 24V AC 2 x 25mm Blank – Side Located 	<p>QUICK ACCESS™</p> <p>BL-QA-211 2 X PL11 watt Flat Glazed</p> <p>BL-QA-311 3 x PL11 watt Flat Glazed</p> <p>BL-QA-211-24V 3 x PL11 watt - 24V AC</p> <p>Suits all industry standard bollards</p>
	<p>CONVERSION BL43™ (BLBASE12)</p> <ul style="list-style-type: none"> 3mm Galvanised Mild Steel Conversion Base Manufactured to fit BLBASE01 Frame Flat Glazed Hinged Window Available 2 x PL11 watt, 3 x PL11 watt, 24V AC 	<p>CONVERSION BL43™ (BLBASE12)</p> <p>BL-BASE43 2 X PL11 watt Flat Glazed</p> <p>BL-BASE45 3 x PL11 watt Flat Glazed</p> <p>BL-BASE01 Galvanised Steel Frame to suit BLBASE44</p> <p>Suits all industry standard bollards</p>
	<p>SURFACE™</p> <ul style="list-style-type: none"> 3mm Galvanised Mild Steel Base Flat Glazed Slimline robust surface mounted baselight Cost effective solution for use with existing ragbolt fixings, requires little or no excavation Available 2 x PL11 watt, 3 x PL11 watt, 24V AC 	<p>SURFACE™</p> <p>BL-SUR-211-F 2 X PL11 watt Flat Glazed</p> <p>BL-SUR-311-F 3 x PL11 watt Flat Glazed</p> <p>Suits all industry standard bollards</p>